

# Nokia 1200 Data Sheet



## Market Introduction:

Q2 2007

## Mobile Phones Category:

Entry – Connect

## Technical Profile:

System:	Dualband EGSM900/1800 and GSM850/1900
User Interface:	Series 30
Dimensions:	102 mm x 44.1 mm x 17.5 mm (L x W x H)
Volume:	67.3 cc
Weight:	76.9 g
Standby time:	Up to 390 h
Talk time:	Up to 7 h
Display:	96 x 68, B/W display with green backlight
Battery:	Nokia Battery BL-5CA

## Key Features:

- New improved flashlight
- Ease-of-Use
- Phone sharing with multi phonebook and call duration to manage call cost
- Dust resistant keypad
- 32 chord polyphonic ringing tones together with MP3-grade tones

## Additional Features:

- Demo application accessible both with and without SIM mode

## Chargers:

- Nokia Compact Charger AC-3
- Nokia Compact Charger AC-5
- Nokia Travel Charger AC-4

## Inbox colors available:

Black, Blue

## Standard Sales Package includes:

- Nokia 1200 handset
- Nokia Battery BL-5CA
- Nokia Compact Charger AC-3
- User guide

## Enhancements:

- Xpress-on™ Covers CC-241D
- Nokia Battery BL-5C
- Nokia Travel Charger AC-4, Nokia Compact Charger AC-5
- Nokia Stereo Headset HS-40 and Nokia Stereo Headset HS-47
- Car accessories: Nokia Mobile Charger DC-4
- Nokia Charger Adapter CA-44
- TTY Adapter HAD-11

Copyright © 2007 Nokia. All rights reserved. Nokia and Nokia Connecting People are registered trademarks of Nokia Corporation. Java is a trademark of Sun Microsystems, Inc. Bluetooth is a registered trademark of Bluetooth SIG, Inc. Other product and company names mentioned herein may be trademarks or tradenames of their respective owners.

Specifications are subject to change without notice. The availability of particular products may vary by region. Variation in operation times will occur depending on SIM card, network and usage settings, usage style and environments. Services and some features may be dependent on the network and/or SIM card as well as on the compatibility of the devices used and the content formats supported.

**NOKIA**  
Connecting People