

Nokia WiFi Beacon 19

Tri-band Wi-Fi 7 mesh Wi-Fi for the multi-gigabit home

The Nokia WiFi Beacon 19 extends multi-gigabit broadband service throughout the entire home using the latest industry standards. The Beacon 19 uses Wi-Fi EasyMesh™ to create a Wi-Fi mesh backbone in the home and User Services Platform (USP/TR-369), TR-181 and Data Elements™ to provide remote visibility to CSPs for troubleshooting and Wi-Fi optimization. Coverage can be expanded by adding up to five additional Beacon 19's to the network using dynamic 6 GHz back-haul and/or wired Ethernet for seamless roaming throughout the home. The Beacon 19's advanced software ensures the best possible Wi-Fi performance. New, value-add services (like cybersecurity) can be installed on the Beacon 19 using Linux Containers for additional revenue generation. With Beacon 19, the subscriber gets an intelligent self-organizing mesh system that can be self-managed using the Nokia WiFi Mobile App.

The Nokia WiFi Beacon 19 is a tri-band Wi-Fi 7 mesh system with Wi-Fi Alliance (WFA) compliant Wi-Fi EasyMesh, enhanced by Nokia value added features. The Nokia WiFi Beacon 19 will take the role of wireless router with access to the broadband network and the wireless mesh network can be extended further with additional Beacon 19 units. Nokia Corteca Device Software creates a self-healing, self-optimizing network. It includes intelligent channel selection, band steering, client steering and backhaul management to provide the best Wi-Fi performance. Through Data Elements, the most important performance indicators of the Wi-Fi network are reported for troubleshooting and Wi-Fi optimization.

Optionally, the Nokia WiFi Beacon 19 can be managed by the Nokia Corteca Home Controller through the Broadband Forum's User Services Platform (USP/TR-369).



Nokia WiFi Beacon 19 (front view)



Nokia WiFi Beacon 19 (rear view)



The associated Console presents the help desk agents with a holistic view of the in-home network to assist them with easy identification and instantaneous resolution of issues as well as offering recommendations for operator upsell opportunities. The Console also improves network operations with Wi-Fi optimization and monitoring through high granularity of radio resource management (RRM) algorithms and reporting.

The Nokia WiFi Mobile App provides home users with an intuitive and simplified interface for trouble-free management of their home network and Wi-Fi. It also provides advanced functions such as guest Wi-Fi management and parental controls.

CSPs can offer new, value-add services to their customers, leveraging Nokia's ecosystem of app developers. The Beacon 19 supports the latest, fully integrated cybersecurity application from F-Secure which is delivered as a containerized application.

Features

- Tri-band concurrent Wi-Fi 7 (BE19000), compatible with all earlier generations of Wi-Fi
- One 1G/2.5G/5G/10G Base-T WAN interface with RJ45 connector
- One 100M/1G/2.5G/5G/10G Base-T LAN interface with RJ45 connector
- Two 10M/100M/1G Base-T LAN interfaces with RJ45 connector
- EasyMesh enhanced by Nokia value added features
- Optimized for multicast video streaming
- TR-069 and TR-369 Remote Management
- Support for Linux containers (LXC) and TR-157

Benefits

- Latest Wi-Fi 7 technology supports 320 MHz channel width and 4K QAM
- Multi-link operation (MLO) brings higher throughput and lower latency

- Tri-band, leveraging 2.4 GHz, 5 GHz and 6 GHz, with 4x4 MIMO on each band
- Can form a mesh network with Nokia WiFi Beacon 19 with wired or wireless mesh backhauling
- Self-healing, self-optimizing mesh network
- Seamless roaming for IEEE 802.11k/v capable and legacy clients
- Client steering, channel optimization
- High quality of service (QoS) video over Wi-Fi
- Ease of setup and user intuitive information
- New, revenue generating applications can be installed through Linux containers

Technical specifications

Physical

- Height: 240 mm (9.4 in)
- Width: 125 mm (4.9 in)
- Depth: 125 mm (4.9 in)
- Weight: 1.23 kg (2.7 lb)

Installation

- Desktop mounting

Operating environment

- Temperature: -5°C to 45°C (23°F to 113°F)
- Relative humidity: 5% to 95%, non-condensing

Power requirements

- Local powering with 12 V DC input (external AC/ DC adapter)
- Power consumption: minimum 13.9 W; maximum 36 W

Ethernet interfaces

- One 1G/2.5G/5G/10G Base-T interface with RJ-45 connector for WAN
- One 100M/1G/2.5G/5G/10G Base-T interface with RJ-45 connector for LAN side
- Two 10M/100M/1G Base-T interfaces with RJ-45 connector for LAN side

WLAN interfaces

- Supports 4x4 802.11b/g/n/ax/be 2.4 GHz wireless LAN (WLAN) interface with support for a channel bandwidth of 20 and 40MHz
- Supports 4x4 802.11 a/n/ac/ax/be 5 GHz WLAN interface with support for a channel bandwidth of 20, 40, 80 and 160MHz
- Supports 4x4 802.11 ax/be 6 GHz WLAN interface with support for a channel bandwidth of 20, 40, 80, 160 and 320MHz
- Support Multi-User Multiple Input, Multiple Output (MU-MIMO)
- Support Multi-User Orthogonal Frequency Division Multiple Access (MU-OFDMA)
- Maximum effective isotropic radiated power (EIRP) on 2.4 GHz up to 1000 mW, on 5 GHz up to 2000 mW, on 6 GHz up to 2000 mW
- Wi-Fi Protected Access (WPA) support including Pre-Shared Key (WPA-PSK), WPA2 and WPA3
- Media access control (MAC) filters
- In OFDMA mode, Resource Unit (RU) fills the entire frequency bandwidth. Supports up to 8 Resource Units (RU) being used at the same time in 2.4 GHz and 5GHz WLAN; up to 16 Resource Units (RU) being used at the same time in 6GHz WLAN.
- Supports channel puncturing function which does not apply in Dynamic Frequency Selection (DFS) and Contention Based Protocol (CBP) functions.

Supported frequency bands (country-specific restrictions apply):

- 2.400-2.4835 GHz
- 5.150-5.850 GHz
- 5.945-7.125 GHz

Router mode

- IPv4 and IPv6 connectivity: Dual stack, stateless and stateful auto-configuration, DHCPv6 prefix delegation
- Point-to-Point Protocol over Ethernet (PPPoE) and IP over Ethernet (IPoE)
- Network Address Translation (NAT), port forwarding, demilitarized zone (DMZ) and firewall
- Dynamic Host Configuration Protocol (DHCP), domain name system (DNS) proxy and dynamic domain name system (DDNS)
- Internet Group Management Protocol (IGMP) v2/v3 proxy
- Virtual private network (VPN) pass-through for Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP) and IPSec
- Flexible video delivery options over Ethernet or wireless
- TR-069 for remote management with support for TR-181 data model
- TR-369/USP support for remote management

LED

- Simple and intuitive status indication by single multi-color LED in front of device

Buttons

- Power on/off
- Wi-Fi Protected Setup (WPS)
- Device reset

Safety and electromagnetic interference (EMI)

- Protection of over voltage/current

Regulatory compliances

- ETL/CB
- FCC
- ISED
- CE/UKCA



About Nokia

At Nokia, we create technology that helps the world act together.

As a B2B technology innovation leader, we are pioneering networks that sense, think and act by leveraging our work across mobile, fixed and cloud networks. In addition, we create value with intellectual property and long-term research, led by the award-winning Nokia Bell Labs.

Service providers, enterprises and partners worldwide trust Nokia to deliver secure, reliable and sustainable networks today – and work with us to create the digital services and applications of the future.

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

© 2024 Nokia

Nokia OYJ
Karakaari 7
02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Document code: (October) CID214139