

Nokia 7215 IXS-A1 Interconnect System

Release 25

The high-performance, fixed-configuration Nokia 7215 IXS-A1 system is designed to manage data center leaf and spine connectivity requirements for telecommunication providers, AI and cloud providers, and mission-critical enterprise environments. It offers 10GE and 1GE interfaces for intra-fabric out-of-band management.

Overview

High-bandwidth servers are driving the need for greater port speeds and density in data center architectures. Similarly, the need for more power-efficient and state-of-the-art NOS design is driving the modernization of network aggregation and interconnect within data centers.

The 7215 IXS-A1 is optimized for management connectivity in data center designs. It delivers a robust and comprehensive set of capabilities, including IP routing, Layer 2, QoS, telemetry and model-driven management.

The 7215 IXS-A1 is 1RU high with a system capacity of 88 Gb/s full duplex (FD). It is equipped with 48 x 10/100/1000 Mb/s RJ45 ports and 4 x 1/10G SFP+ ports.

The 7215 IXS-A1 is offered in distinct integrated variants, each configured with either redundant AC or redundant DC power supplies and with front-to-back or back-to-front airflow.



7215 IXS-A1

The 7215 IXS-A1 supports an optional Modular GPU Accelerated Server (MGX) rack adapter, enabling seamless integration with MGX-accelerated computing racks and speeding up the deployment of GPU-based AI and high-performance computing infrastructure.



Nokia Service Router Linux (SR Linux)

Nokia Service Router Linux (SR Linux) is a Linux®-based open, extensible and resilient NOS that enables scalability, flexibility and efficiency in data center and WAN environments. The Nokia 7215 IXS-A1 implements Nokia SR Linux.

SR Linux is a key component of the Nokia Data Center Fabric solution, which also includes the Nokia Fabric Services System and the Nokia Data Center hardware platforms.

Ground-up, model-driven architecture delivers extensibility

In cloud-scale data center networks, the primary challenges are scalability and ease of operations. SR Linux is designed from the ground up with a management architecture that meets the demands of a model-driven world where visibility—and the scalability and granularity of that visibility—are paramount.

SR Linux features a completely model-driven architecture for flexible and simplified management and operations. SR Linux delivers an extensible and open infrastructure that allows applications to define and declare their own schemas, enabling the retrieval of fine-grained system state and setting of configuration.

Modular, state-sharing architecture

SR Linux uses an unmodified Linux kernel as the foundation on which applications share state via a publish/subscribe (pub/sub) architecture.

The Nokia pub/sub architecture is implemented using generalized Remote Procedure Call (gRPC), protocol buffers (protobufs) and the Nokia Impart Database (IDB).

The Nokia IDB is a lightweight database that is optimized to handle high volumes of messages while protecting against any one application slowing down the whole system.

Field-proven protocol stacks

SR Linux leverages field-proven routing protocol technologies developed over decades of large-scale IP networking from the Nokia Service Router Operating System (SR OS), bringing a strong pedigree of reliability and performance to modern data center environments.

Enterprise, AI and cloud provider, and telecom-communication provider data centers are increasingly adopting leaf-spine fabric designs using enhanced IP routing with Multiprotocol-Border Gateway Protocol (MPBGP), EVPN, Virtual Extensible LAN (VXLAN), MPLS and segment routing protocols. By using field-proven protocol stacks, data center operators can immediately benefit from the stability, scalability and interoperability of a resilient NOS.

Superior CLI programmability and integration of third-party applications

Operations teams can leverage command line interface (CLI) plugins to completely customize the way the CLI operates, plugging in Linux commands or pulling the state/configuration from various locations.

SR Linux allows third-party applications to be fully integrated into the system and given all the same benefits as Nokia applications. This includes consistent configuration via YANG, telemetry support, life-cycle management and visibility of system resources.

SR Linux offers a state-of-the-art NetOps Development Kit (NDK) for data center teams to develop new applications and operational tools in the language of their choice with deep programmatic access to, and control of, the entire system.

Data center fabric automation

Nokia offers an intent-based data center fabric management and automation platform that delivers reliable operations, simplified life-cycle management and is adaptable to all data center and cloud environments.

For details see the [web page](#).



Software features

The Nokia 7215 IXS-A1 supports, but is not limited to, the following SR Linux software features:

For additional details about SR Linux, including NOS architecture and differentiators, see the [Nokia Service Router Linux data sheet](#).

Open Linux support

- Support for unmodified Linux kernel
- Access to Linux tools, patching and packaging
- Linux control groups (cgroups v2)

Layer 2 features

- Dot1q and untagged sub-interfaces on bridged sub-interfaces
- Ethernet IEEE 802.1Q (VLAN) with support for jumbo frames
- Link aggregation: Link Aggregation Group (LAG) and Link Aggregation Control Protocol (LACP)
- Link Layer Discovery Protocol (LLDP) on all interfaces
- Media access control (MAC) loop prevention
- MAC storm control
- Virtual routing and forwarding (VRF): MAC-VRF
- MAC access control lists (ACLs) with validation: accept, reject and log actions

Layer 3 features

- IPv4/v6 routing
- BGP with iBGP/eBGP: Support for IPv4/v6, including:
 - Core Prefix independent convergence
 - 4-byte autonomous system number
 - Route reflector
 - Dynamic BGP
 - BGP unnumbered
 - eBGP multi-hop
 - Add-paths for IPv4 and IPv6 routes

- IS-IS v4/v6
- Open Shortest Path First: OSPFv2 and OSPFv3
- Static routes for IPv4/v6
- Equal cost multi-path
- IPv6 flow label hashing
- VRF: Multiple VRF support
- Maintenance modes
- Bi-directional forwarding detection (BFD), micro BFD (mBFD)
- Interfaces: Loopback interfaces, Integrated Routing and Bridging (IRB)
- Routing policy:
 - Structured rules for accepting, rejecting and modifying routes that are learned and advertised to routing peers
 - Routes can be matched based on prefix lists, autonomous system (AS) path regular expressions, BGP communities, Address Family Indicator/Subsequent Address Family Indicator (AFI/SAFI) protocol, etc.
 - Route leaking between network instances
- Layer 3/Layer 4 ACLs with validation; accept, reject and log actions

QoS

- QoS classification and marking based on DiffServ Code Point (DSCP)
- QoS classification and marking based on IEEE 802.1p

System management and automation

- Native model-driven architecture, configuration candidates, exclusive mode, checkpoints, rollbacks
 - Support for SR Linux and OpenConfig¹ data models
- Management interfaces: gNMI, gRPC Routing Information Base Interface (gRIBI), JSON-RPC and CLI (transactional, Python CLI and CLI plugins)
- gRPC network operations interface (gNOI)
- gRPC Network Security Interface (gNSI)
- Per-user configurable options for CLI
- Local Authentication, Authorization and Accounting (AAA) with Role-Based Access Control (RBAC)
- Remote Authentication Dial-In User Service (RADIUS) support for AAA
- Terminal Access Controller Access Control System (TACACS+) AAA via privilege levels
- Password complexity policies and lockout management
- Access to common Linux utilities: Bash, cron and Python
- Syslog RFC 5424
- Telemetry:
 - Subscription-based telemetry for modeled data structures, either on change or sampled
 - sFlow
 - Logging infrastructure
- Telemetry-driven event management
- Python-based Zero Touch Provisioning (ZTP)
- Address management: Dynamic Host Configuration Protocol (DHCP) v4/v6 relay
- DHCP v4/v6 server with static allocations
- Interactive mirroring
- Unified Forwarding Tables (UFT) profiles

NetOps Development Kit (NDK)

- gRPC and protobuf-based interface for tight integration
- Leverages SR Linux model-driven architecture
- Direct access to other application functionality, e.g., forwarding information base (FIB), LLDP and BFD
- Native support for streaming telemetry

Resiliency

- Support for redundant fan and power configurations
- Graceful restart client for BGPv4/v6

Security

- Distributed and aggregated ACLs and policers for control and management plane
- Layer 2 through Layer 4 Control Plane Policing (CoPP)
- IPv6 router advertisements guard

System scale and performance

Platform-specific scale and performance information is available and can be provided on request.

Learn more

To learn more about the Data Center Fabric solution, see the [web page](#).

¹ Future software release



Technical specifications

Table 1. Nokia 7215 IXS-A1 specifications

Feature	Parameter
System throughput	88 Gb/s
Full duplex (FD)	
Ports	4 x SFP+ 48 x RJ45
Hardware support (maximum ports per chassis)	
10GE	4
1GE	4
1000/100/10 Mb/s	48
Management ports	1 x 1000Base-T
USB ports	1 x USB 2.0
Console ports	1x RJ45
Processor	4-core ARM
Memory	4GB DDR4
Memory buffer size	3 MB
Storage	16GB eMMC
Power	Integrated; Fixed, redundant AC power or redundant DC power systems (orderable variants) AC: 100V to 240V DC: -48 V/ -60V 100 W AC 100 W DC
Fan modules	Integrated; Fixed, redundant front-to-back or back-to-front airflow systems (orderable variants)
Dimensions	Height: 4.37 cm (1.72 in); 1 RU Width: 43.85 cm (17.26 in) Depth: 25.38 cm (9.99 in)
Weight	3.54 kg (7.8 lb)
Mounting options	2-post; 4-post with rail kit option
Discrete Trusted Platform Module (TPM)	Yes
Normal operating temperature range (sustained)	0°C to +40°C (32°F to +104°F)
Shipping and storage temperature range	-20°C to +70°C (-4°F to +158°F)
Normal humidity	5% to 95%, non-condensing



Table 2. MGX rack adapter specifications (optional)

The MGX rack adapter is designed for use in an MGX-accelerated computing rack. The adapter includes an airflow vent, a DC bus-bar connector, a power switch, DC power connectors, and an integrated ground cable with an attachment lug. The Nokia 7215 IXS-A1 and the MGX rack adapter are installed in the rack using sliding rails.

Feature	Parameter
Adapter without system and slide rails installed	
Dimensions	Height: 1.67 in. (4.25 cm) Width: 17.26 in. (43.85 cm) Depth: 23 in. (58.45 cm)
Weight	7.58 lb (3.42 kg)
Adapter with system and slide rails installed	
Dimensions	Height: 1.72 in. (4.37 cm) Width: 19.07 in. (48.45 cm) Depth: 33.46 in. (85 cm)
Weight	Excluding outer rack rails: 16.19 lb (7.33 kg) Including outer rack rails: 22.24 lb (10.08 kg)

Standards compliance²

Environmental

- ETSI EN 300 019-2-1; Storage Tests, Class 1.2
- ETSI EN 300 019-2-2; Transportation Tests, Class 2.3
- ETSI EN 300 019-2-3; Operational Tests, Class 3.2
- ETSI EN 300 753; Acoustic Noise, Class 3.2
- GR-3160-CORE

Electromagnetic compatibility

- AS/NZS CISPR 32 Class A
- BSMI CNS 15936 Class A
- BT GS-7
- EN 55035
- EN 55032 Class A
- ETSI EN 300 132-1 (AC)
- ETSI EN 300 132-2 (DC)
- ETSI EN 300 386

- ETSI ES 201 468
- FCC Part 15 Class A
- ICES-003 Class A
- IEC CISPR 32 Class A
- IEC CISPR 35
- IEC/ EN 61000-3-2
- IEC/EN 61000-3-3
- IEC/EN 61000-6-2
- IEC/EN 61000-6-4
- KCC Korea - Immunity KS C 9835
- KCC Korea - Emissions KS C 9832
- VCCI Class A

Safety

- AS/NZS 62368-1
- FDA CDRH 21-CFR 1040
- IEC/BS/EN 60825-1
- IEC/BS/EN 60825-2
- IEC/UL/CSA/BS/EN 62368-1

² System design intent is according to the listed standards.
Refer to product documentation for detailed compliance status.



Directives and regional approvals

- Directive 2011/65/EU RoHS (including Commission Delegated Directive EU 215/863)
- Directive 2012/19/EU WEEE
- Directive 2014/30/EU EMC
- Directive 2014/35/EU LVD
- CE Mark: Europe
- CRoHS: China RoHS
- KC Mark: South Korea
- RCM Mark: Australia
- UKCA Mark: United Kingdom
- VCCI Mark: Japan
- BSMI Mark: Taiwan

About Nokia

At Nokia, we create technology that helps the world act together.

As a B2B technology innovation leader, we are pioneering networks that sense, think and act by leveraging our work across mobile, fixed and cloud networks. In addition, we create value with intellectual property and long-term research, led by the award-winning Nokia Bell Labs, which is celebrating 100 years of innovation.

With truly open architectures that seamlessly integrate into any ecosystem, our high-performance networks create new opportunities for monetization and scale. Service providers, enterprises and partners worldwide trust Nokia to deliver secure, reliable and sustainable networks today – and work with us to create the digital services and applications of the future.

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

© 2026 Nokia

Nokia OYJ
Karakoari 7
02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Document code: (January) CID214158