

800G ZR/ZR+ pluggable coherent modules

Compatible coherent optics for the Nokia 7250 IXR and 7750 SR

Relentless demand for increased capacity at a lower cost per bit is compelling operators to continuously upgrade and optimize their IP-optical networks. Nokia coherent routing utilizes digital coherent optics (DCOs) equipped in router interface ports to connect directly over DWDM wavelengths.

Modules and applications

800G ZR -2dBm 0/70 °C is a standardized, interoperable 800G coherent interface specification available in the router-pluggable QSFP-DD format. Developed by the Optical Internetworking Forum (OIF) and released in October 2024, 800ZR is profile-optimized for high-density access and point-to-point DCI applications. Depending on fiber link characteristics, it is designed to deliver 800 Gb/s on a single dark fiber span over a distance of up to approximately 50 km without amplification. With external amplification, it supports up to 32 800G channels or 64 400G WDM channels in the C-band over distances up to 150 km.

800G ZR+ 0dBm 0/70 °C expands the application space for router-pluggable coherent optics in QSFP-DD format. Compared to 800ZR, it offers enhanced optical performance through advanced soft-decision FEC, flexible 100G–800G operating modes, and improved shaping that enables extended reach using lower-order modulation where supported. In 800G mode, and depending on fiber link characteristics, 800G ZR+ is designed to achieve distances of more than 1000 km with external amplification. Even greater distances are possible at 400G rates. Additionally, 800ZR+ can traverse a limited number of reconfigurable optical add-drop multiplexer (ROADM) nodes, enabling efficient router bypass in amplified DWDM networks when necessary.



Technical specifications

Operating environment

- Temperature: 0-70°C (32°F to 158°F)
- Relative humidity: 5% to 95%

Table 1. Nokia 800G Coherent tunable DWDM part numbers

Part Number	Description	Interface
3HE18112AA	QSFP112-DD 800G ZR -2dBm 0/70C	800GBase-ZR
3HE18113AA	QSFP112-DD 800G ZR+ 0dBm 0/70C	800GBase-ZR+

800G ZR -2dBm specifications (part number 3HE18112AA)

Table 2. 800G operation mode

3HE18112AA - QSFP112-DD 800G ZR -2dBm 0/70C				
Parameter	Unit	800G		
Compatibility mode (config)		Long haul		
Host mode Framing				
Media code		6C		
Breakout		c1-800g	c2-400g	c8-100g
Host format		800GAUI-8-L-C2M	400GAUI-4-L-C2M	100GAUI-1-L-C2M
Baud rate	Gbaud	118.20		
Data rate	Gbit/s	800		
Signal Spectral Width - Min Tx Spectral excursion	GHz	-1.5		
Signal Spectral Width - Max Tx Spectral excursion	GHz	1.5		
Roll off parameter of the Tx pulse shaping filter (raised-cosine)	β	0.19		
Single or Dual Polarization		Dual		
Number of subcarriers		1		
Inband Transmit OSNR (db)	dB	37		
Out of Band Transmit OSNR (db)	dB	38		
Minimum configurable Transmit power	dBm	-10		
Maximum configurable Transmit power	dBm	-2		
Minimum configurable Frequency	GHz	191.7 THz		
Maximum configurable Frequency	GHz	196.1 THz		
Configurable frequency resolution	GHz	3.125 GHz		
Minimum receiver OSNR	dB	26.6		
Pre FEC BER required to achieve 1E-15 post FEC BER		0.02		
FEC type		OFEC		
Minimum Grid Spacing (effective channel spectral band-width)	GHz	150		
Minimum receiver signal power	dBm	-9		
Maximum receiver signal power	dBm	+1		
Maximum allowed Chromatic Dispersion	ps/nm	3000		
Chromatic Dispersion penalty for maximum compensation	dB	0.5		
Maximum allowed Polarization Mode Dispersion	ps	108		
Polarization Mode Dispersion penalty for max. compensation	dB	0.5		
Maximum allowed Polarization Dependent Loss	dB	4		
Polarization Dependent Loss penalty for max. compensation	dB	4		
Polarization Dependent Loss penalty curve	dB	0.5dB OSNR penalty @ 1 dB PDL 1.0dB OSNR penalty @ 2 dB PDL 4.0dB OSNR penalty @ 4 dB PDL		
Maximum allowed State of Polarization change	krad/s	175		
State of Polarization penalty for maximum tracking speed	dB	3		
State of Polarization penalty curve	dB	3dB penalty @ 175krads/s		
Maximum Receiver Total Power	dBm	+1		
Power consumption	W	29		

Table 3. 400G operation mode

3HE18112AA - QSFP112-DD 800G ZR -2dBm 0/70C		
Parameter	Unit	400G
Compatibility mode (config)		Long haul
Host mode Framing		
Media code		OpenROADM
App selection number		64
Breakout		c1-400g-aii4 C4-100g-aii1
Host format		400GAUI-4-L-C2M 100GAUI-1-L-C2M
Baud rate	Gbaud	118.20
Data rate	Gbit/s	400
Signal Spectral Width - Min Tx Spectral excursion	GHz	-1.5
Signal Spectral Width - Max Tx Spectral excursion	GHz	1.5
Roll off parameter of the Tx pulse shaping filter (raised-cosine)	β	0.19
Single or Dual Polarization		Dual
Number of subcarriers		1
Inband Transmit OSNR (db)	dB	37
Out of Band Transmit OSNR (db)	dB	38
Minimum configurable Transmit power	dBm	-10
Maximum configurable Transmit power	dBm	-2
Minimum configurable Frequency	GHz	191.7 THz
Maximum configurable Frequency	GHz	196.1 THz
Configurable frequency resolution	GHz	3.125 GHz
Minimum receive OSNR	dB	17.9
Pre FEC BER required to achieve 1E-15 post FEC BER		0.02
FEC type		OFEC
Minimum Grid Spacing (effective channel spectral bandwidth)	GHz	150
Minimum receiver signal power	dBm	-12
Maximum receiver signal power	dBm	+1
Maximum allowed Chromatic Dispersion	ps/nm	58000
Chromatic Dispersion penalty for maximum compensation	dB	0.5
Maximum allowed Polarization Mode Dispersion	ps	108
Polarization Mode Dispersion penalty for maximum compensation	dB	0.5
Maximum allowed Polarization Dependent Loss	dB	4
Polarization Dependent Loss penalty for maximum compensation	dB	4
Polarization Dependent Loss penalty curve	dB	0.5dB OSNR penalty @ 1 dB PDL 1.0dB OSNR penalty @ 2 dB PDL 4.0dB OSNR penalty @ 4 dB PDL
Maximum allowed State of Polarization change	krad/s	500
State of Polarization penalty for maximum tracking speed	dB	3
State of Polarization penalty curve	dB	3dB penalty @ 500krads/s
Maximum Receiver Total Power	dBm	+1
Power consumption	W	29

800G ZR+ 0dBm specifications (part number 3HE18113AA)

Table 4. 800G operation mode

3HE18113AA QSFP112-DD 800G ZR+ 0dBm 0/70C				
Parameter	Unit	800G		
Compatibility mode (config)		Long haul		
Network mode framing		ZR+		
Media code		F7		
Breakout		c1-800g	c2-400g	c8-100g
Host format		800GAUI-8-L-C2M	400GAUI-4-L-C2M	100GAUI-1-L-C2M
Baud rate	Gbaud	131.30		
Data rate	Gbit/s	800		
Signal Spectral Width - Min Tx Spectral excursion	GHz	-1.5		
Signal Spectral Width - Max Tx Spectral excursion	GHz	1.5		
Roll off parameter of the Tx pulse shaping filter (raised-cosine)	β	0.175		
Single or Dual Polarization		Dual		
Number of subcarriers		1		
Inband Transmit OSNR (db)	dB	37		
Out of Band Transmit OSNR (db)	dB	38		
Minimum configurable Transmit power	dBm	-10		
Maximum configurable Transmit power	dBm	0		
Minimum configurable Frequency	GHz	191.7 THz		
Maximum configurable Frequency	GHz	196.1 THz		
Configurable frequency resolution	GHz	3.125 GHz		
Minimum receive OSNR	dB	24.7		
Pre FEC BER required to achieve 1E-15 post FEC BER		0.02		
FEC type		OFEC		
Minimum Grid Spacing (effective channel spectral band-width)	GHz	150		
Minimum receiver signal power	dBm	-9		
Maximum receiver signal power	dBm	+1		
Maximum allowed Chromatic Dispersion	ps/nm	24000		
Chromatic Dispersion penalty for maximum compensation	dB	0.5		
Maximum allowed Polarization Mode Dispersion	ps	97		
Polarization Mode Dispersion penalty for max. compensation	dB	0.5		
Maximum allowed Polarization Dependent Loss	dB	4		
Polarization Dependent Loss penalty for max. compensation	dB	4		
Polarization Dependent Loss penalty curve	dB	0.5dB OSNR penalty @ 1 dB PDL 1.0dB OSNR penalty @ 2 dB PDL 4.0dB OSNR penalty @ 4 dB PDL		
Maximum allowed State of Polarization change	Krad/s	300		
State of Polarization penalty for maximum tracking speed	dB	3		
State of Polarization penalty curve	dB	3dB penalty @ 300krads/s		
Maximum receiver total power	dBm	+1		
Power consumption	W	31		

Table 5. 400G operation mode

3HE18113AA QSFP112-DD 800G ZR+ 0dBm 0/70C		
Parameter	Unit	800G
Compatibility mode (config)		Long haul
Ntwk mode framing		ZR+
Media code		EC
Breakout		c1-400g-aii4 c4-100g-aii1
Host format		400GAUI-4-L-C2M 100GAUI-1-L-C2M
Baud rate	Gbaud	131.30
Data rate	Gbit/s	400
Signal Spectral Width - Min Tx Spectral excursion	GHz	-1.5
Signal Spectral Width - Max Tx Spectral excursion	GHz	1.5
Roll off parameter of the Tx pulse shaping filter (raised-cosine)	β	0.3
Single or Dual Polarization		Dual
Number of subcarriers		1
Inband Transmit OSNR (db)	dB	37
Out of Band Transmit OSNR (db)	dB	38
Minimum configurable Transmit power	dBm	-10
Maximum configurable Transmit power	dBm	0
Minimum configurable Frequency	GHz	191.7 THz
Maximum configurable Frequency	GHz	196.1 THz
Configurable frequency resolution	GHz	3.125 GHz
Minimum receive osnr	dB	18
Pre FEC BER required to achieve 1E-15 post FEC BER		0.02
FEC type		OFEC
Minimum Grid Spacing (effective channel spectral band-width)	GHz	150
Minimum receiver signal power	dBm	-12
Maximum receiver signal power	dBm	+1
Maximum allowed Chromatic Dispersion	ps/nm	24000
Chromatic Dispersion penalty for maximum compensation	dB	0.5
Maximum allowed Polarization Mode Dispersion	ps	97
Polarization Mode Dispersion penalty for max. compensation	dB	0.5
Maximum allowed Polarization Dependent Loss	dB	4
Polarization Dependent Loss penalty for max. compensation	dB	4
Polarization Dependent Loss penalty curve	dB	0.5dB OSNR penalty @ 1 dB PDL 1.0dB OSNR penalty @ 2 dB PDL 4.0dB OSNR penalty @ 4 dB PDL
Maximum allowed State of Polarization change	krad/s	775
State of Polarization penalty for maximum tracking speed	dB	3
State of Polarization penalty curve	dB	3dB penalty @ 775krads/s
Maximum receiver total power	dBm	+1
Power consumption	W	31



About Nokia

At Nokia, we create technology that helps the world act together.

As a B2B technology innovation leader, we are pioneering networks that sense, think and act by leveraging our work across mobile, fixed and cloud networks. In addition, we create value with intellectual property and long-term research, led by the award-winning Nokia Bell Labs, which is celebrating 100 years of innovation.

With truly open architectures that seamlessly integrate into any ecosystem, our high-performance networks create new opportunities for monetization and scale. Service providers, enterprises and partners worldwide trust Nokia to deliver secure, reliable and sustainable networks today – and work with us to create the digital services and applications of the future.

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

© 2026 Nokia

Nokia OYJ
Karakaari 7
02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Document code: (April) CID215394