Nokia 7220 IXR-D series Interconnect Routers

Release 26

The Nokia 7220 IXR-D series platforms are designed for the leaf and spine layers of data center fabrics, delivering up to 12.8 Tb/s capacity and up to 400GE interfaces, providing high-scale interconnectivity for AI and cloud providers, telecommunication providers, and mission-critical enterprise environments.

Overview

AI, high-performance computing (HPC), cloud and other data-intensive workloads are transforming data center networks, driving demand for greater speed, scalability, efficiency and automation. Network operators need reliable, high-capacity switching platforms with high-speed interfaces to support today's requirements and scale for future network growth.

The Nokia 7220 IXR-D series offers versatile platforms for enterprise and modern data center builders, making it well-suited for leaf and spine deployments in the front-end networks of CLOS data center architectures.

Scaling from 88 Gb/s full duplex (FD) to 12.8 Tb/s FD, the 7220 IXR-D series delivers high-density 400GE, 200GE, 100GE, 50GE, 40GE and 10GE interfaces in a compact 1RU form factor. It supports a wide a range of optics — including 400G QSFP-DD, 100G QSFP28, 25G SFP28 and 10G SFP+ with flexible optical breakouts —for intra-fabric and workload connectivity.



7220 IXR-D1



7220 IXR-D2L



7220 IXR-D3L



7220 IXR-D4



7220 IXR-D5

Powered by Nokia Service Router (SR) Linux, the 7220 IXR-D series is available in five variants, each distinguished by optical interfaces and system throughput capabilities.

Leveraging SR Linux, the 7220 IXR-D series delivers a comprehensive set of advanced features that support scalable multi-tenant solutions in data centers. By utilizing EVPN VxLAN tunnels, it provides efficient Layer 2 and Layer 3 overlay networking, while EVPN multicast support optimizes Layer 2 multicast delivery across the fabric.

In addition, the 7220 IXR-D series offers traffic-steering capabilities through forwarding policies based on user-defined criteria, making the data-center network more intelligent and adaptable.

Supported platforms

7220 IXR-D1

The 7220 IXR-D1 is 1 RU high with a system capacity of 88 Gb/s FD. It is equipped with 48 x 10/100/1000 Mb/s RJ45 ports and 4 x 10G SFP+ ports.

The SFP+ ports of the 7220 IXR-D1 include hardware support for native 10GE interfaces. It is optimized for leaf-spine designs, which require server connectivity at 1GE speeds.

The 7220 IXR-D1 supports two power supplies with 1+1 redundancy using either AC or DC power options. The system supports both front-to-back and back-to-front airflow configuration with three N+1 hot-swappable fans.

7220 IXR-D2L

The 7220 IXR-D2L platform is 1 RU high with a system capacity of 2.0 Tb/s FD. It is equipped with 48 x 25G SFP28 ports, 8 x 100G QSFP28 connectors and 2 x 10G SFP+ ports. The QSFP28 connectors support breakout options for 4 x 25G and 4 x 10G speeds.

All QSFP28 connectors include hardware support for native 100GE and 40GE interfaces. The SFP28 ports include hardware support for native 25GE, 10GE and 1GE interfaces. These options provide high-performance intra-fabric uplinks, storage and server connectivity.

The 7220 IXR-D2L platform supports two power supplies with 1+1 redundancy using either AC or DC power options.

The 7220 IXR-D2L platform supports front-to-back and back-to-front airflow configuration with six N+1 hot-swappable fans.

7220 IXR-D3L

The 7220 IXR-D3L platform is 1 RU high with a system capacity of 3.2 Tb/s FD. It is equipped with 32 x 100G QSFP28 connectors supporting 2 x 50G, 4 x 25G and 4 x 10G optical breakouts, along with 2 x 10G SFP+ ports.

All QSFP28 connectors include hardware support for native 100GE and 40GE interfaces, enabling exceptional flexibility in a variety of leaf or spine deployment configurations. The SFP+ ports include hardware support for native 10GE speeds.

The 7220 IXR-D3L platform supports two power supplies with 1+1 redundancy using either AC or DC power options.

The 7220 IXR-D3L platform supports front-to-back and back-to-front airflow configuration with six N+1 hot-swappable fans.

7220 IXR-D4

The 7220 IXR-D4 is 1 RU high with a system capacity of 6.0 Tb/s FD. It is equipped with 28 x 100G QSFP28 connectors and 8 x 400G QSFP-DD connectors supporting 4 x 100G, 2 x 200G, 4 x 25G, 4 x 10G optical breakouts.

All QSFP-DD connectors include hardware support for native 400GE, 100GE, 50GE and 40GE interfaces. These connectors provide exceptional flexibility in a variety of leaf or spine deployment configurations.

The 7220 IXR-D4 supports two power supplies with 1+1 redundancy using either AC or DC power options.

The system supports front-to-back and back-to-front airflow configuration with six N+1 hot- swappable fans.

7220 IXR-D5

The 7220 IXR-D5 is 1 RU high with a system capacity of 12.8 Tb/s FD. It is equipped with 32 x 400G QSFP-DD connectors supporting 4 x 100G, 2 x 200G, 2 x 100G, 4 x 50G, 4 x 25G, 4 x 10G optical breakouts, and 2 x 10G SFP+ ports.

All QSFP-DD connectors include hardware support for native 400GE, 200GE, 100GE, 50GE and 40GE interfaces, enabling exceptional flexibility in a variety of leaf or spine deployment configurations. The SFP+ ports include hardware support for native 10GE speeds.

The 7220 IXR-D5 supports two power supplies with 1+1 redundancy using either AC or DC power options.

The system supports front-to-back and back-to-front airflow configuration with six N+1 hot-swappable fans.

Nokia Service Router Linux

Nokia SR Linux is a Linux®-based open, extensible and resilient NOS that enables scalability, flexibility and efficiency in data center and cloud environments. The Nokia 7220 IXR-D series implements Nokia SR Linux.

SR Linux is a key component of the Nokia Data Center Fabric solution, which also includes the Nokia Event-Driven Automation (EDA) and the Nokia Data Center hardware platforms.

Ground-up, model-driven architecture delivers extensibility

In cloud-scale data center networks, the primary challenges are scalability and/or ease of operations. SR Linux is designed from the ground up with a management architecture that meets the demands of a model-driven world where visibility—and the scalability and granularity of that visibility—are paramount.

SR Linux features a completely model-driven architecture for flexible and simplified management and operations. SR Linux delivers an extensible and open infrastructure that allows applications to define and declare their own schemas, enabling the retrieval of fine-grained system state and setting of configuration.

Modular, state-sharing architecture

SR Linux uses an unmodified Linux kernel as the foundation on which applications share state via a publish/subscribe (pub/sub) architecture. The Nokia pub/sub architecture is implemented using generalized Remote Procedure Call (gRPC), protocol buffers (protobufs) and the Nokia Impart Database (IDB).

The Nokia IDB is a lightweight database that is optimized to handle high volumes of messages while protecting against any one application slowing down the whole system.

Field-proven protocol stacks

SR Linux leverages field-proven protocol stacks from the Nokia Service Router Operating System (SR OS), which has a strong pedigree in IP routing. Enterprise, service provider and webscale data centers are increasingly adopting leaf-spine fabric designs using enhanced IP routing with Multiprotocol-Border Gateway Protocol (MP-BGP), EVPN, Virtual Extensible LAN (VXLAN), MPLS and segment routing protocols. By using field-proven protocol stacks, data center planning and operations teams can immediately benefit from the stability, scalability and interoperability of a resilient NOS.

Scalable streaming telemetry

SR Linux was built with an open, scalable telemetry framework at its core, internally using gRPC, gRPC Network Management Interface (gNMI) and protobufs. Because SR Linux is natively model driven, it is immediately ready for streaming telemetry without requiring any translation layers.

Superior CLI programmability and integration of third-party applications

Operations teams can leverage command line interface (CLI) plugins to completely customize the way the CLI operates, plugging in Linux commands or pulling the state/configuration from various locations.

SR Linux allows third-party applications to be fully integrated into the system and given all the same benefits as Nokia applications. This includes consistent configuration via YANG, telemetry support, life-cycle management and visibility of system resources.

SR Linux offers a state-of-the-art NetOps Development Kit (NDK) for data center teams to develop new applications and operational tools in the language of their choice with deep programmatic access to, and control of, the entire system.

AI data center networking

The Nokia AI data center networking solution provides the reliability, simplicity and flexibility you need to build and deploy network infrastructures that can meet the requirements of current and future AI workloads.

Nokia is at the forefront of defining and testing the evolution of Ethernet for AI. Nokia is an active member of the Ultra Ethernet Consortium (UEC) which is bringing enhancements that make Ethernet the best choice for AI network infrastructures. Nokia's solution is AI-ready and UEC-compatible with support for Remote Direct Memory Access over Converged Ethernet (RoCEv2) and Data Center Quantized Congestion Notification (DCQCN). Nokia is also implementing key features within the latest UEC spec.

Nokia also follows and participates in Open Compute Project (OCP) which is driving various new standards for Ethernet. One notable specification is Multipath Reliable Connection (MRC) that builds upon the existing RoCEv2 Ethernet framework to enable scalable, high-performance AI/ML workloads over multipath best-effort networks by specifying architectural extensions for multipath load balancing, reliability, and congestion control.

Nokia Event-Driven Automation

The Nokia Event-Driven Automation (EDA) is a Kubernetes-native, declarative, intent-based automation platform that automates the entire data center fabric lifecycle—from Day 0 design through to Day 2+ operations.

Built on a cloud-native microservices architecture, the EDA continuously reconciles desired and observed state using real-time streaming telemetry to ensure the network operates as intended. It abstracts multivendor complexity, enables network-wide transactional changes with rollback, and embeds a real-time Digital Twin for safe validation before deployment.

The declarative, intent-based framework and the automation capabilities of the EDA framework are only made possible by leveraging a modern NOS that offers an open, model-driven, stream-anything foundation.

By using Nokia SR Linux modern streaming telemetry approach for the NOS, the EDA framework has timely and efficient access to more granular data across the entire fabric. This data can then be used to understand the state of the network, which is essential for event-driven applications to determine if the network is behaving according to their intent. This approach is also highly scalable, which is essential in today's networks.

Nokia EDA complements SR Linux, supporting advanced management and automation capability to help design, deploy and operate back-end and front-end networks for AI workloads.

Technical specifications

Table 1. Nokia 7220 IXR-D series specifications

Feature	7220 IXR-D1	7220 IXR-D2L	7220 IXR-D3L	7220 IXR-D4	7220 IXR-D5
System throughput: Full duplex (FD)	88 Gb/s	2.0 Tb/s	3.2 Tb/s	6.0 Tb/s	12.8 Tb/s
Connectors	• 4 x 10G SFP+ • 48 x 10/100/1000 Mb/s RJ45	• 8 x 100G QSFP28/ QSFP+ • 48 x 25G SFP28 • 2 x 10G SFP+	• 32 x 100G QSFP28/ QSFP+ • 2 x 10G SFP+	• 28 x 100G QSFP28 • 8 x 400G QSFP-DD	• 32 x 400G QSFP-DD • 2 x 10G SFP+
Optical breakouts	NA	4 x 25G, 4 x 10G	2 x 50G, 4 x 25G, 4 x 10G	4 x 100G, 2 x 200G, 4 x 25G, 4 x 10G	4 x 100G, 2 x 200G, 2 x 100G, 4 x 50G, 4 x 25G, 4 x 10G
Hardware support (maximum ports per chassis)					
400GE	NA	NA	NA	8	32
200GE	NA	NA	NA	12	64
100GE	NA	8	32	48	128
50GE	NA	16*	62	46*	144
40GE	NA	8	32	36	32
25GE	NA	48	124	40	128
10GE	4	48	124	40	128
1GE	NA	48	NA	NA	NA
1000/100/10 Mb/s	48	NA	NA	NA	NA
Management ports	1 x 1000BASE-T	1 x 1000BASE-T	1 x 1000BASE-T	1 x 1000BASE-T	1 x 1000BASE-T
USB ports	1 x USB2.0	1 x USB2.0	1 x USB2.0	1 x USB2.0	1 x USB2.0
Console port	1 x RJ45	1 x RJ45	1 x RJ45	1 x RJ45	1 x RJ45
Processor	4-core x86	4-core x86	4-core x86	8-core x86	8-core x86
Memory	8G DDR4	16G DDR4	16G DDR4	16G DDR4	16G DDR4
Memory buffer size	8 MB	32 MB	32 MB	82 MB	132 MB
SSD	16G SLC	32G MLC	32G MLC	50G MLC	50G MLC
Power	1+1 redundant AC: 100 V to 240 V DC:-48 V/-60 V 240 W AC 550 W DC	1+1 redundant AC: 100 V to 240 V DC:-48 V/-60 V HVDC: 190 V to 310 V 650 W AC 650 W DC	1+1 redundant AC: 100 V to 240 V DC:-48 V/-60 V HVDC: 190 V to 310 V 650 W AC 650 W DC	1+1 redundant AC: 100 V to 240 V DC:-48 V/-60 V 650 W AC 800 W DC	1+1 redundant AC: 100 V to 240 V DC:-48 V/-60 V 1500 W AC 1600 W DC
Fan modules	3 fans, N+1 redundant Front-to-back or back-to-front airflow	6 fans, N+1 redundant Front-to-back or back-to-front airflow	6 fans, N+1 redundant Front-to-back or back-to-front airflow	6 fans, N+1 redundant Front-to-back or back- to-front airflow	6 fans, N+1 redundant Front-to-back or back-to-front airflow
Hot-swappable fan modules	Yes	Yes	Yes	Yes	Yes
Hot-swappable power supplies	Yes	Yes	Yes	Yes	Yes

* Future deliverable

Nokia 7220 IXR-D series specifications (continued)

Feature	7220 IXR-D1	7220 IXR-D2L	7220 IXR-D3L	7220 IXR-D4	7220 IXR-D5
Dimensions	Height: 4.35 cm (1.75 in); 1 RU Width: 43.85 cm (17.26 in) Depth: 40 cm (15.75 in) Fits in standard 19-in mounting rack	Height: 4.31 cm (1.70 in); 1 RU Width: 43.84 cm (17.26 in) Depth: 53.6 cm (21.10 in) Fits in standard 19-in mounting rack	Height: 4.32 cm (1.70 in); 1 RU Width: 43.84 cm (17.26 in) Depth: 51.5 cm (20.28 in) Fits in standard 19-in mounting rack	Height: 4.35 cm (1.75 in); 1 RU Width: 43.84 cm (17.26 in) Depth: 59 cm (23.23 in) Fits in standard 19-in mounting rack	Height: 4.35 cm (1.75 in); 1 RU Width: 43.84 cm (17.26 in) Depth: 59 cm (23.23 in) Fits in standard 19-in mounting rack
Weight	7.5 kg (16.53 lb) (unpopulated) 9.5 kg (20.94 lb) (fully populated)	7.36 kg (16.23 lb) (unpopulated) 10 kg (22 lb) (fully populated)	6.65 kg (14.66 lb) (unpopulated) 9.38 kg (20.68 lb) (fully populated)	7.88 kg (17.37 lb) (unpopulated) 10.93 kg (24.09 lb) (fully populated)	8.57 kg (18.89 lb) (unpopulated) 11.85 kg (26.12 lb) (fully populated)
4-post mounting	Yes; rail kit option	Yes; rail kit option	Yes; rail kit option	Yes; rail kit option	Yes; rail kit option
Discrete Trusted Platform Module (TPM)	Yes	Yes	Yes	Yes	Yes
Normal operating temperature range	0°C to +40°C (32°F to +104°F) sustained	0°C to +40°C (32°F to +104°F) sustained	0°C to +40°C (32°F to +104°F) sustained	0°C to +40°C (32°F to +104°F) sustained	0°C to +40°C** (32°F to +104°F) sustained
Shipping and storage temperature	-40°C to +70°C (-40°F to +158°F)	-40°C to +70°C (-40°F to +158°F)	-40°C to +70°C (-40°F to +158°F)	-40°C to +70°C (-40°F to +158°F)	-40°C to +70°C (-40°F to +158°F)
Normal humidity	5% to 95%, non-condensing	5% to 95%, non-condensing	5% to 95%, non-condensing	5% to 95%, non-condensing	5% to 95%, non-condensing

** Certain airflow configurations and the use of reduced case temperature optics may reduce the maximum operating temperature

Software features

The 7220 IXR-D series supports, but is not limited to, the following SR Linux software features:[1]

Open Linux support

- Support for unmodified Linux kernel
- Access to Linux tools, patching and packaging
- Third party containers running on SR Linux
- Linux control groups (cgroupsv2)

Platform features

- Dynamic Ternary Content Addressable Memory (TCAM) table allocation
- Unified Forwarding Tables (UFT) profiles

Layer 2 features

- Dot1q and untagged sub-interfaces, including VLAN ranges on bridged sub-interfaces
- Ethernet IEEE 802.1Q (VLAN) with support for jumbo frames
- Link aggregation: Link Aggregation Group (LAG) and Link Aggregation Control Protocol (LACP)
- Link Layer Discovery Protocol (LLDP) on all interfaces
- Media access control (MAC) loop prevention
- MAC storm control
- MAC virtual routing and forwarding (VRF): MAC-VRF
- MAC-VRF network instance with IRB interface
- MAC access control lists (ACLs) with validation: accept, reject and log actions
- Internet Group Management Protocol (IGMP) snooping and Multicast Listener Discovery (MLD) snooping in Layer 2 broadcast domains

1 This section provides an overview of key features supported. Some platforms may have feature exclusions or exceptions. Consult Nokia documentation for detailed feature support and interdependencies.

Layer 3 features

- IPv4/v6 routing
  - Static, aggregate routes for IPv4/v6
  - IP unnumbered interfaces
  - Dual-stack Interior Gateway Protocol (IGP)
  - Multi-topology IS-IS v4/v6
  - Open Shortest Path First (OSPFv2 and OSPFv3)
  - Multiprotocol BGP (MP-BGP)
- BGP with iBGP/eBGP:
  Support for IPv4/v6, including:
  - Core Prefix independent convergence
  - 4-byte autonomous system number
  - Route reflector
  - Dynamic BGP
  - BGP unnumbered
  - eBGP multi-hop
  - Add-paths for IPv4 and IPv6 routes
- Equal cost multi-path with consistent and resilient hashing and configurable hash fields
- IPv6 flow label hashing
- VRF: Multiple VRF support
- Maintenance modes
- Interfaces: Loopback interfaces, Integrated Routing and Bridging (IRB)
- Proxy Address Resolution Protocol (ARP)/ neighbor discover (ND)
- Routing policy:
  - Structured rules for accepting, rejecting and modifying routes that are learned and advertised to routing peers
  - Routes can be matched based on prefix lists, autonomous system (AS) path regular expressions, BGP communities, Address Family Indicator/Subsequent Address Family Indicator (AFI/SAFI) protocol, etc.
  - Route leaking between network instances
- Layer 3/Layer 4 ACLs with validation; accept, reject and log actions

Network virtualization

- EVPN with VXLANv4 encapsulation
- EVPN Layer 2 and Layer 3 connectivity
- EVPN all-active multi-homing; single-active multi-homing for Layer 2 and Layer 3
- EVPN Anycast Multi-Homing (draft-rabnag-bess-evpn-anycast-aliasing)
- EVPN host route mobility
- Provider edge-to-customer edge (PE-CE) BGP path attribute propagation in EVPN
- EVPN IP aliasing
- Gateway-IP based load balancing for EVPN IP Prefix route
- SMET based IGMP/MLD proxy, including multi-homing synchronization for EVPN-VXLAN (RFC 9251)
- Optimized Inter-Subnet Multicast (OISM) for EVPN-VXLAN (RFC 9625)
- OISM PEG (PIM to EVPN gateway) function for EVPN-VXLAN

QoS

- Intelligent packet classification, including IPv4, IPv6 match-criteria-based classification
- Ingress per forwarding class sub-interface policing
- Queuing/scheduling:
  - Strict priority
  - Weighted Round Robin (WRR)
  - Weighted Random Early Detection (WRED)
  - Explicit Congestion Notification (ECN)
- QoS classification and marking based on DiffServ Code Point (DSCP)
- QoS classification and marking based on IEEE 802.1p
- Priority Flow Control (PFC)
- Ingress DSCP remarking
- Multi-field classification

Flow monitoring

- sFlow

Operations, Administration and Maintenance (OAM)

- Bi-directional forwarding detection (BFD), micro-BFD (mBFD)
- Link Layer Discovery Protocols (LLDP)
- Mirroring sources from interface/sub-interface or ingress ACL
- Mirroring destinations to local interface or remote interface

System management and automation

- Native model-driven architecture, configuration candidates, exclusive mode, checkpoints, rollbacks
  - Support for SR Linux and OpenConfig[2] data models
- Management interfaces: gNMI, gRPC Routing Information Base Interface (gRIBI), NETCONF, JSON-RPC and CLI (transactional, Python CLI and CLI plugins)
- YANG modeled actions (CLI, NETCONF, gRPC and JSON-RPC)
- gRPC network operations interface (gNOI)
- gRPC Network Security Interface (gNSI)
- Global and per-user CLI environment configuration
- Local Authentication, Authorization and Accounting (AAA) with Role Based Access Control (RBAC)
- Remote Authentication Dial-In User Service (RADIUS) support for AAA
- Terminal Access Controller Access Control System (TACACS+) AAA with VSAs or privilege levels
- Password complexity policies and lockout management
- Access to common Linux utilities: Bash, cron and Python
- Logging infrastructure for local and remote logs including Syslog RFC 5424 support
- Facility alarms for equipment status
- Telemetry:
  - Subscription-based telemetry for modeled data structures, either on change or sampled
  - sFlow
- Telemetry-driven event management
- Python-based Zero Touch Provisioning (ZTP)
- Address management: Dynamic Host Configuration Protocol (DHCP) v4/v6 relay
- DHCP v4/v6 server with static allocations

NetOps Development Kit (NDK)

- gRPC and protobuf-based interface for tight integration
- Leverages SR Linux model-driven architecture
- Direct access to other application functionality, e.g., forwarding information base (FIB), LLDP and BFD
- Native support for streaming telemetry

Resiliency

- Support for redundant fan and power configurations
- Warm reboot to perform soft reset or trigger an in-service software upgrade (ISSU)
  - Nonstop forwarding (NSF)
  - Graceful restart client for BGPv4/v6

Security

- Distributed and aggregated ACLs and policers for control and management plane
- Layer 2 through Layer 4 Control Plane Policing (CoPP)
- IPv6 router advertisements guard

Timing and synchronization[3]

- Built-in Stratum 3E clock
- ITU-T Synchronous Ethernet (SyncE)
- IEEE 1588v2 PTP
  - Boundary clock (BC)
  - Profiles: ITU-T G.8275.1, G.8275.2
  - PTP encapsulation: Ethernet, IPv4/IPv6
- RFC 5905 Network Time Protocol (NTP)

2 Future software release

3 Supported only on the 7220 IXR-D5

AI backend data center networking[4]

- RDMA over converged Ethernet (RoCEv2)
- Explicit Congestion Notification (ECN)
- Priority Flow Control (PFC)
- Data Center Quantized Congestion Notification (DCQCN)
- Compatibility with evolving UEC and OCP capabilities

Standards compliance[5]

Environmental and NEBS

- ATIS 0600015.03
- ETSI EN 300 019-2-1; Storage Tests, Class 1.2
- ETSI EN 300 019-2-2; Transportation Tests, Class 2.3
- ETSI EN 300 019-2-3; Operational Tests, Class 3.2
- ETSI EN 300 753; Acoustic Noise, Class 3.2[6]
- GR-3160-CORE
- GR63 Core Level 2
- VZ.TPR.9205

Safety

- AS/NZS 62368-1
- FDA CDRH 21-CFR 1040
- IEC/BS/EN 60825-1
- IEC/BS/EN 60825-2
- IEC/UL/CSA/BS/EN 62368-1

Electromagnetic compatibility

- AS/NZS CISPR 32 Class A
- BSMI CNS 13438 Class A (IXR-D1, IXR-D5)
- BSMI CNS 15936 Class A (IXR-D2L, IXR-D3L, IXR-D4)
- BT GS-7
- EN 55035
- EN 55032 Class A
- ETSI ES 201 468
- ETSI EN 300 132-1 (AC)
- ETSI EN 300 132-2 (LVDC)
- ETSI EN 300 386
- FCC Part 15 Class A
- FTZ 1 TR9 (Deutsche Telekom)
- GR1089
- ICES-003 Class A
- IEC CISPR 32 Class A
- IEC CISPR 35
- IEC/EN 61000-3-2
- IEC/EN 61000-3-3
- IEC/EN 61000-4-2 ESD
- IEC/EN 61000-4-3 Radiated Immunity
- IEC/EN 61000-4-4 EFT
- IEC/EN 61000-4-5 Surge
- IEC/EN 61000-4-6 Conducted Immunity
- IEC/EN 61000-4-11 Voltage Interruptions
- IEC/EN 61000-6-2
- IEC/EN 61000-6-4
- ITU-T K.20
- KCC Korea - Immunity KS C 9835/KN35
- KCC Korea - Emissions KS C 9832/KN32
- VCCI-CISPR 32 Class A

4 Some platforms may have feature exclusions or exceptions.

5 System design intent is according to the listed standards. Refer to product documentation for detailed compliance status.

6 Certain airflow configurations will impact acoustics. Please contact Nokia for details

Directives and regional approvals

- Directive 2011/65/EU RoHS
- Directive 2012/19/EU WEEE
- Directive 2014/30/EU EMC
- Directive 2014/35/EU LVD
- ISO 14001
- ISO 9001
- CE Mark: Europe
- CRoHS: China RoHS
- KC Mark: South Korea
- RCM Mark: Australia
- UKCA Mark: United Kingdom
- VCCI Mark: Japan
- TL9000

System scale and performance

Platform-specific scale and performance information is available and can be provided on request.

Learn more

To learn more about the Nokia Data Center Fabric solution, see the web page.

About Nokia

At Nokia, we create technology that helps the world act together.

As a B2B technology innovation leader, we are pioneering networks that sense, think and act by leveraging our work across mobile, fixed and cloud networks. In addition, we create value with intellectual property and long-term research, led by the award-winning Nokia Bell Labs.

Service providers, enterprises and partners worldwide trust Nokia to deliver secure, reliable and sustainable networks today – and work with us to create the digital services and applications of the future.

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

© 2026 Nokia

Nokia OYJ
Karakaari 7
02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Document code: (November) CID207599